





SIWAREX load cells are ideal in almost any industrial sector - food-processing, steel-making, chemical and pharmaceutical, to name a few.

With the diverse construction types and comprehensive, graded load classes ranging from 3 kilograms to 500 tons, you are sure to find the right load cell for your application.

Avoid installation troubles by complementing your load cells with SIWAREX mounting accessories. Mounting accessories get you ready for operation in the shortest possible period.

# Load cells: the foundation of every scale

#### SIWAREX load cells

	SIWAREX WL230 BB	SIWAREX WL230 SB	SIWAREX WL250	SIWAREX WL260	SIWAREX WL270	SIWAREX WL280	SIWAREX WL290
		00		0 5			Alle
Order no	7MH5106	7MH5107	7MH5105	7MH5102/03/04/ 16/17/18/20/23	7MH5108/10/14	7MH5113	7MH5122
Туре	Bending beam for platform and hopper scales	Shear beam load cell for platform and hopper scales, overhead track scales	S-type load cell for tension and pressure applica- tions, hanging and hopper scales, hybrid scales	Single point load cell for platform scales	Compression load cell for hopper scales, overhead truck scales, vehicle scales	Ring torsion load cell for platform and hopper scales, conveyor belt scales, roller table scales	Double shear beam load cell for big platform, hopper, and vehicle scales
Key features	• Rated load from 10 kg to 500 kg • C3 to OIML R60 • IP68	Rated load from 0.5 to 5t     C3 to OIML R60     IP68	• Rated load from 50 kg to 10 t • C3 to OIML R60 • IP67	<ul> <li>Rated load from 3 kg to 200 kg</li> <li>C3 to OIML R60</li> <li>IP66, IP67, IP68, IP69K</li> </ul>	Rated load from 2.8 t to 500 t     C3 to OIML R60     IP66/IP68	• Rated load from 60 kg to 60 t • C3 to OIML R60 • IP66/IP68	• Rated load from 13.6 t to 34 t • C3 to OIML R60 • IP67

## SIWAREX mounting units and junction boxes

	SIWAREX WL230 BB	SIWAREX WL230 SB	SIWAREX WL270 CP	SIWAREX WL270 K	SIWAREX WL280 RN	SIWAREX WL290	Junction boxes
					Tay's		The said
Order No.	7MH5707	7MH4133 7MH5707	7MH5708 7MH5710	7MH3115	7MH4130 7MH4125 7MH4115	7MH5722	7MH4710
Туре	Base plate and elastomer bearing for platform and hopper scales, roller table scales	Compact mounting unit for platform and hopper scales, roller table scales	Compact mounting unit for hopper scales	Self-aligning bearing for hopper scales, silo scales	Compact installation unit and arm, Elastomer bearings for platform and hopper scales, roller table scales	Mounting unit for platform and hopper scales	Junction boxes to connect several load cells to one SIWAREX weighing system
Key features	Rated load from 500 kg to 5 t     Material: stainless steel and neoprene	• Rated load from 10 kg to 500 kg, 0.5 t to 5 t • Material: stainless steel	Rated load from 2t to 50 t, 100 t     Material: stainless steel	Rated load from 2.8 t to 500 t     Material: steel, enameled	Rated load from 60 kg to 60 t     Material: stainless steel and neoprene	Rated load from 13,6 kg to 34 t     Material: Nickel-plated steel	Material: aluminium or stainless steel     IP66

# Load cells: the foundation of every scale

#### SIWAREX load cells

	SIWAREX WL230 BB	SIWAREX WL230 SB	SIWAREX WL250	SIWAREX WL260	SIWAREX WL270	SIWAREX WL280	SIWAREX WL290
		00	100	0 65			Allow
Order no	7MH5106	7MH5107	7MH5105	7MH5102/03/04/ 16/17/18/20/23	7MH5108/10/14	7MH5113	7MH5122
Туре	Bending beam for platform and hopper scales	Shear beam load cell for platform and hopper scales, overhead track scales	S-type load cell for tension and pressure applica- tions, hanging and hopper scales, hybrid scales	Single point load cell for platform scales	Compression load cell for hopper scales, overhead truck scales, vehicle scales	Ring torsion load cell for platform and hopper scales, conveyor belt scales, roller table scales	Double shear beam load cell for big platform, hopper, and vehicle scales
Key features	• Rated load from 10 kg to 500 kg • C3 to OIML R60 • IP68	• Rated load from 0.5 to 5t • C3 to OIML R60 • IP68	• Rated load from 50 kg to 10 t • C3 to OIML R60 • IP67	<ul> <li>Rated load from 3 kg to 200 kg</li> <li>C3 to OIML R60</li> <li>IP66, IP67, IP68, IP69K</li> </ul>	Rated load from 2.8 t to 500 t     C3 to OIML R60     IP66/IP68	• Rated load from 60 kg to 60 t • C3 to OIML R60 • IP66/IP68	• Rated load from 13.6 t to 34 t • C3 to OIML R60 • IP67

## SIWAREX mounting units and junction boxes

	SIWAREX WL230 BB	SIWAREX WL230 SB	SIWAREX WL270 CP	SIWAREX WL270 K	SIWAREX WL280 RN	SIWAREX WL290	Junction boxes
					1-15		The state of
Order No.	7MH5707	7MH4133 7MH5707	7MH5708 7MH5710	7MH3115	7MH4130 7MH4125 7MH4115	7MH5722	7MH4710
Туре	Base plate and elastomer bearing for platform and hopper scales, roller table scales	Compact mounting unit for platform and hopper scales, roller table scales	Compact mounting unit for hopper scales	Self-aligning bearing for hopper scales, silo scales	Compact installation unit and arm, Elastomer bearings for platform and hopper scales, roller table scales	Mounting unit for platform and hopper scales	Junction boxes to connect several load cells to one SIWAREX weighing system
Key features	Rated load from 500 kg to 5 t     Material: stainless steel and neoprene	• Rated load from 10 kg to 500 kg, 0.5 t to 5 t • Material: stainless steel	Rated load from 2t to 50 t, 100 t     Material: stainless steel	Rated load from 2.8 t to 500 t     Material: steel, enameled	Rated load from 60 kg to 60 t     Material: stainless steel and neoprene	Rated load from 13,6 kg to 34 t     Material: Nickel-plated steel	Material: aluminium or stainless steel     IP66